

Horizon HD-TC8

Horizon HD-TC8

The all new HD-TC8 is the latest generation meter for the Global uptake of VSAT installations, measuring BPSK / QPSK / 8PSK, DigiCipher II and Turbo Code formats. Specifically designed for the new "Tooway internet service on Hotbird 13E KA band".

Designed with a generous storage of up to 256 transponders, including the flexibility of 16 user customisable selections for onsite unique carriers. The transmission signals can be isolated with this precise and accurate installation tuner, reducing the time to detect the downlink path and hence frustration in the often challenging environments of VSAT use.

As with this type of system, battery supply is important for field and remote locations, so this Meter comes built with a long life high-output Lithium-Polymer rechargeable battery pack, supplying 15V DC at 2400mAh, capable of providing more than 6 hours continuous run time.

Horizon's menu template of "keep it clear and simple" has continued with this meter, to include features such as Spectrum, Constellation Diagrams, Bit Error analysis, Carrier-to Noise and true MER expressed in dB, all in an intuitive and easy to use format.

The HD-TC8 comes as a complete kit with mains charger, car charger and USB cable for data transfer and satellite settings update from our website. Support and downloads for the HD-TC8 are available via a dedicated website. No internet registration is required, charge your meter and you are ready to go.



Features:

- LNB voltage selectable up to 22 V, 750 mA maximum
- Field-replaceable F barrels for RF IN and DC OUT
- Bit rates from 1 MBaud to 30 MBaud
- Frequency range 950 to 2150 MHz
- Input levels from -70 dBm to -25 dBm
- Bargraph RF level display with values in dBm or dBuV
- Bargraph display of signal quality for peaking and polarization
- Display of RF levels over swept frequency range (spectrum)
- Display of I and Q values by constellation diagram
- Writes and recognises DiSEqC 2.0 commands
- Easy download of transponder information by area/operator
- Multiple-entry performance log for off-line upload
- Quick-check LNB/cable diagnostic by current and RF level

HORIZON

For a reliable solution!

www.horizonhge.com

Horizon Global Electronics
First Floor Office, Allen House,
Edinburgh Way, Harlow, Essex, CM20 2HJ

T: +44 (0) 1279 417005
F: +44 (0) 1279 417025
E: sales@horizonhge.com

